



Black Pearl

Solvent transfer paper



Black Pearl allows you to create professional transfers on dark garments. The nonwoven effect offers a high quality transfer paper solution.

printing instructions

Print only on Solvent printers and offset printers with solvent, solvent light, mild solvent or eco-solvent inks. Recommended profile for Roland VersaCamm Series = Vinyl-SOFOGLP2, Print Standard (720x720)

application instructions

Print the image onto the coated side of the rolls. Cut the outlines and remove the unprinted film. Place a tape foil onto the motive and rub with a squeegee to the image as well against the tape foil will be adhere. Fix the tape foil with the printed image onto the substrate, press for 30-35 seconds and peel hot.

heat press specifications



Black Pearl

Solvent transfer paper



30-35 Sec

190°C · 375°F

heavy pressure

washing

Turn the textile inside out and wash at max. 40° C/ 100° F. Do not bleach. Iron only on the reverse side or cover the transfer with a backing paper.

Temperatures in Fahrenheit and thicknesses in mil are given as approximate values. All data are standard values. The information in this specification sheet is based on findings obtained in practice. Because of the high number of factors which can have an effect during handling and application, customer tests will be required. A legally binding guarantee of specific properties is not to be inferred from our specifications. The information given here may be subject to change without notice.



Joseph-von-Fraunhofer-Str. 3b • 52477 Alsdorf
Telefon +49 (0) 24 04-91 99-60/-70 • Telefax +49 (0) 24 04-91 99 18
<http://www.mtct.de> • e-Mail: products@mtct.de